

NABCO Entrances - GT1175 Telescopic Slide Door - ORDER FORM

\$=USA Dollar

Revision

2024

1.6.T

Quote:

Page:

of

Company:

Distributor #:

Door #:

Date:

Job Name:

PO #:

Contact:

Drop Ship to:

Ship Method:

Date to Ship:

Notes:

Type of Unit:

Single

Fixed Sidelite

Bi-part

Full Open

Hand of Unit: (viewed from panic breakaway side)

Right hand

Left hand

Frame Size:

Width (in)

Header Height (in)

Clear Door Opening Width (in)

Transom:

YES

<or>

NO

Total Frame Height Including Transom (std.=91-1/2")

Number of Verticals in Transom

Door/Panel Glass Thickness

Transom Glass Thickness

1/4" (std.)

1/4" (std.)

Other

Other

Other Glass Thickness Options: 1/2", 9/16", 5/8", 3/4", 7/8", 1"

Finish:

Clear (204)

Dark bronze (313)

Special anodize

Black

Powder Coat

Paint

Prep for paint by distributor

Color

Threshold:

NONE (Fixed Sidelite ONLY)

1/2" Standard Between Jambs (Full Open Only)

1/4" Through Door Opening (Full Open Only)

1/2" Under Jambs* (Full Open Only)

*Does the Total Frame Height entered in Frame Size include height of threshold?

YES

<or>

NO

Bottom Rail:

Standard

6-1/2"

10"

Other

Quantity

Drawing #

Additions/Changes:

Panic Device:

Surface applied push bar exit hardware

Recessed push bar exit hardware

Paddle exit hardware (Fixed Sidelite)

Electric Lock:

Fail Safe Electric Lock

Fail Secure Electric Lock

Armored Strike:

Armored Strike

Door Closer:

of Door Closer(s) instead of Limit Arm

Extra Holding Beam:

of Additional Holding Beams (1 Beam Standard)

Tie Rods:

Tie Rods Required (Y/N)

Nose Caster:

Req. for panels over 200 lbs. or wider than 42"

Sensors:

Sidelite Protection

Angled spacer for Acusensor M

Rain Cover for Acusensor M

Upgrade Sensor:

Conceal, Acuzone, i-One, or ULTIMO

Alarm Contact:

Select Yes or No Alarm/Security Contact

Cart Bars:

Aluminum Cart Bars (specify panels for Bars)

Muntin Bars:

2" (Standard)

Other: 4", 8", 6-3/8" (Standard Recessed Panic)

None

Standard Height 42-1/4" F.F. - top

Special location - F.F. - top

Additional Muntin - F.F. - top

Medium Stiles:

Change to Medium Stile (4")

Switches:

Key Switches in lieu of Rocker Switch

Change Rocker Switches location (include diagram)

Exit Indicator:

Exit Indicator

Add.Sidelite(s):

of Additional sidelite(s)

Width (in)

Height (in)

Muntins

Jamb Tubes:

2" x 7"

None Required

Note: On Telescopic doors, a threshold jamb to jamb is necessary on a full open unit. Any threshold option is available for fixed units.