

NABCO ICU DOORS

OVERVIEW



High-Quality Doors for All of Your Healthcare Needs

- Wide opening width for easier access
- Flush bolt-free system not requiring additional steps to breakout
- Maintenance-friendly design resolving issues against improper installations
- Smoke rated package to meet UL1784 & NFPA 105 requirements
- Tested to over one million use cycles for proven reliability
- Designed for easy operation in the hospital environment
- Highest quality ICU/CCU doors available on the market
- Privacy glass and self-closer option available for 2400 series manual doors

NABCO's ICU doors are ideally suited for **intensive care and cardiac care units (ICU/CCU)** where airborne germs must be kept from spreading to other areas, and extensive access areas are required for the trouble-free transport of beds, gurneys, and other medical equipment. With the available air infiltration package, our ICU doors are ideal for rooms where air quality must be maintained in case of fire and "infection control" to prevent germs from spreading and preserve a sterile environment.

Our line of ICU Doors is available with Automatic and Manual operation in various sizes to fit almost any application, and with options for parts of our line of ICU Doors to meet the requirements of almost any application, including touch-free activation, anti-microbial coatings, electrified panels for privacy glass, and more.

Product Information				
Type	Manual Door		Automatic Door	
Model	2400M	2400MT	2400A	2400AT
Panels	2	3	2	3
Description	Trackless Full Breakout Manual Sliding Door	Trackless Full Breakout Manual Telescopic Sliding Door	Trackless Full Breakout Automatic Sliding Door	Trackless Full Breakout Automatic Telescopic Sliding Door
Header (W x H)	4 ½" [114] X 5" [127]	7 ¼" [270] x 5" [127]	8" [203] X 5" [127]	10 ¾" [270] x 5" [127]
Frame Width	64" [1626] - 108" [2743]	84" [2134] - 144" [3658]	66" [1676] - 108" [2743]	84" [2134] - 144" [3658]
Frame Height	83" [2108] - 102" [2591]	83" [2108] - 102" [2591]	83" [2108] - 102" [2591]	83" [2108] - 102" [2591]
Clear Door Opening Width	28 ½" [714] - 50 ½" [1273]	48 ½" [1232] - 88 ½" [2248]	28 ½" [714] - 49 ½" [1248]	48 ½" [1232] - 88 ½" [2248]
Jamb Tube	¾" x 4 ½"	1 ¾" x 6 ¾"	1 ¾" x 4 ½"	1 ¾" x 6 ¾"
Standard finish	Clear			
Optional Finishes	Black, Dark Bronze Anodized, Painted, Special Anodized, Clad			
Mounting	Trackless	Trackless	Trackless	Trackless
Sidelite	Full Breakout	Full Breakout	Full Breakout	Full Breakout
Single	Available	Available	Available	Available
Bipart	Available	Not Available	Not Available	Not Available
Standard Features	4" Bottom Rails, 2 ½" Narrow Styles, 2" Horizontal Muntin, Vinyl Weathering Seals, Electrostatic Discharge Grounding			
Available Options*	UL1784 Smoke Package, Positive Latch, 6 ½" & 10" Bottom Rails, Permanent anti-microbial finish, Security hook and latch, Hold-open tied to fire alarm, Door control sensor, 4" Muntin, Self-Closer			
Approvals	UL1784, NFPA105, NFPA101, UL325			

*Not all listed options are available with all configurations. Contact your NABCO representative for details.



Self-Closer (2400)



NABCO ICU Manual Telescopic (2400MT) with Electrified Privacy Glass

Trackless, 1-Step Break-out


Wide frame sizes, for wide door opening and full-breakout for moving patients and equipment.

Smoke Infiltration Rated

UL1784 is the Standard for Air Leakage tests of Door Assemblies and Other Opening Protectives. Order the smoke package to limit air infiltration.

Privacy Glass Options

Designed with electrified privacy glass and integrated mini-blind glass options in mind for patient privacy and security during care.



Design Your New facility with NABCO Doors:

Visit:
<https://www.nabcoentrances.com/products/icuccu-doors/>



Member of the Nabtesco Group



NABCO Entrances Inc.
S82 W18717 Gemini Drive
Muskego, WI 53150
NABCOEntrances.com
info@NABCOEntrances.com
P 877-622-2694

Rev. 4-10-2025