NABCO Entrances - ICU 2100 Series Manual Door - ORDER FORM

$=USA Dollar	Revision
2024	1.3.T

Quote: | Page: | of

Company: | Distributor #: | Door #:

Date: | Job Name:

PO #: | Contact:

Drop Ship to:

Ship Method: | Date to Ship:

Notes:

Type of Unit:

Quantity

Model:

	GT2100R		GT2125R		GT2150R		
	GT2100L		GT2125L		GT2150L		
	GT2100TR		GT2125TR		GT2150TR		
	GT2100TL		GT2125TL		GT2150TL		
	GT2100B		GT2125B		GT2150B		
	GT2100TB		GT2125TB		GT2150TB		

Frame Size:

- Width
- Header Height (slider std. = 88")
- Height Including Transom
- Number of Verticals in Transom
- Clear Door Opening Width

Door/Panel Glass Thickness

- 1/4" (std.)
- 1/2"
- 9/16"
- 5/8"
- 3/4"
- 7/8"
- 1"

Transom Glass Thickness

- 1/4" (std.)
- 1/2"
- 9/16"
- 5/8"
- 3/4"
- 7/8"
- 1"

Finish:

- Clear (204) (Standard)

Special Finishes: Additional Cost/Time

- Special Anodized
- Powder Coat
- Dark Bronze Anodized (313)
- Black Anodized
- Paint (Color)

Threshold: **(applies to 2150 only)**

- Through Door Opening
- Between Jambs
- Under Jambs
- Other

Bottom Rail:

- Standard
- 6-1/2"
- 10"

Jamb Tubes:

- 1-3/4" x 4-1/2" No Pockets (2- and 4-Panel Std.)
- 2" x 7" (Standard for 3- or 6-Panel)
- 1-3/4" x 6-3/8"
- 2" x 5"
- No Jambs Required
- Other (Specify)

Muntin Bars:

- 2" std.
- 4"
- 6-3/8"
- 8"
- No muntins required

- Standard Height 42-1/4" F.F. - top
- Special location - F.F. - top
- Additional Muntin - F.F. - top

Options:

(Standard pulls are the "D" and recessed pulls)

- Recessed Handles (both sides)
- 4570 (Levers Down - Positive Latch)
- Handle + Recessed Pull
- Handle on Both Sides (reduces door opening on 2100 only)
- 4550 Dead Bolt Lever with Exit Indicator
- Medium Stile
- No Panic Breakout
- Delete Sidelites for Surface Applied
- Floor Sweeps
- Pile + Brush Weather Stripping
- Composite panels in bottom of doors
- Self Closing
- Hold Open
- Air Infiltration Package

Note: Air infiltration/smoke infiltration sealing automatically includes 4570 Latching System