# NABCO GT2300 Manual/ICU Swing Door - Quote Request FORM

| $=USA Dollar | Revision |
|---|---|
| 2024 | 1.3.T |

Quote: | Page: | of

Company: | Distributor #: | Door #:

Date: | Job Name:

PO #: | Contact:

Drop Ship to:

Ship Method: | Date to Ship:

Notes:

**Type of Unit:** | **Quantity**

**Model Type "A" or "B" as viewed from swing side:**

- "A" Inactive Door - Active Door
- "B" Active Door - Inactive Door

**Frame Size:**

- Width (Frame & Doors) (99-1/2" Maximum)
- Header Height (Standard 87-5/8", Maximum 125")
- Active door width (panel equipped with Latch Handle)
- Inactive door width (panel equipped with Flush Bolt)

**Door/Panel Glass Thickness**

- 1/4" (std.)
- 1" or other

**Finish:**

- Clear (204) (Standard)

*Special Finishes at Additional Cost*

- Special anodize
- Powder Coat
- Prep for paint by distributor
- Dark bronze (313)
- Paint
- Color

**Threshold:**

- No Threshold (Std)
- Between Jambs
- Under Jambs
- (Included in Height)
- Other

**Bottom Rail:**

- 4" (Standard)
- 5"
- 6-1/2"
- 10"

**Top Rail:**

- 4" (Standard)
- 5"
- 6-1/2"
- 10"

**Note: Door gap at bottom is 1/2" standard**

**Jamb Tubes:**

- Standard (1-3/4" x 4-1/2" - No Pockets)
- 1-3/4" x 6-3/8"
- 2" x 5"
- 2" x 7"
- No Jambs Required
- Header Width for No Jambs

Hinges are on outside edges of jamb tubes

**Muntin Bars:**

- 2" std.
- 4"
- 6-3/8"
- 8"
- No muntins required

**Muntin Height:**

- Standard Height 42-1/4" F.F. - Top
- Special location - F.F. - Top
- Additional Muntin - F.F. - Top

**Options:**

- Medium Stile
- Smoke Rated Required

Some Options Affect Smoke Rating

Composite Panels

| | |
|---|---|
| Check One | All Lites |
| | Bottom Lites |
| | Top Lites |
| Choose Color | Metallic Silver |
| | Bone White |
| | Glossy White |
| | Dark Bronze |
| Choose Finish | Textured |
| | Smooth |