

NABCO GT1500 Convenience Window - ORDER FORM

\$=USA Dollar

Revision

2025

1.2.T

Quote:

Page:

of

Company:

Distributor #:

Door #:

Date:

Job Name:

PO #:

Contact:

Drop Ship to:

Ship Method:

Date to Ship:

Notes:

Type of Unit:

GT1500 -

(architectural drawing #)

Quantity

Bi-part

Single

Additions:

Holding Beam/s

Qty:

Hand of Unit:

Right hand

Left hand

viewed from exterior

Armored Strike

"D" Handle in lieu of Recessed

on Interior Sliding Panels

"4570" Handle in lieu of Recessed

on Interior Panels (P/N 14-10588)

Frame Size:

Width (min. 30" singles - 42" Bi-parts)

Header Height without Transom (std. = 35-3/4") (min. 30")

Height Including Transom

Number of Verticals in Transom

Sliding/Fixed Panel

Glass Thickness

1/4" (std.)

1/2"

9/16"

5/8"

3/4"

7/8"

1"

Finish:

Clear (204)

Dark bronze (313)

Special anodize

Black

Powder Coat

Paint

Prep for paint by distributor

Color

Extended Warranty

2 Years

3 Years

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.

NABCO - GT1400 Folding Door - ORDER FORM

\$=USA Dollar	Revision
2025	1.2.T

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Type of Unit:	
	Single Fold
	Bi-Fold
Hand of Unit:	
	Right hand (door slides to the right when viewed from <u>interior</u>)
	Left hand (door slides to the left when viewed from <u>interior</u>)
Frame Size:	
	Width (in)
	Header Height
	Clear Door Opening Width (in)
Transom:	
	YES <or> NO
	Total Frame Height Including Transom (std.=91-1/2")
	Number of Verticals in Transom

Door/Panel Glass Thickness	Transom Glass Thickness
	1/4" (std.)
	Other

Other Glass Thickness Options: 1/2", 9/16", 5/8", 3/4", 7/8", 1"

Finish:	
	Clear (204)
	Special anodize
	Powder Coat
	Prep for paint by distributor
	Dark bronze (313)
	Black
	Paint
	Color

Threshold:	
	NONE (Standard)
	1/2" Standard Between Jambs
	*Does the Total Frame Height entered in Frame Size include height of threshold?
	YES <or> NO

Quantity	Drawing #
----------	-----------

Additions/Changes:	
Electric Lock:	Fail Safe Electric Lock
	Fail Secure Electric Lock
	Fail Safe Electro-Magnetic Lock
Armored Strike:	Armored Strike
Sensors:	Sidelite Protection
	Angled spacer for Acusensor M
	Rain Cover for Acusensor M
Upgrade Sensor:	Conceal, Acuzone, i-One, or ULTIMO
Alarm Contact:	Select Yes or No Alarm/Security Contact
Jamb Tubes:	None Required
	1-3/4" x 4-1/2" (Standard)

Muntin Bars:	2" (Standard)
	Other: 4", 8", 6-3/8" (Standard Recessed Panic)
	None
	Standard Height 42-1/4" F.F. - top
	Special location - F.F. - top
	Additional Muntin - F.F. - top

Guide Rails:	
	(Qty.) Fold Side (matches finish of door)
Length:	One Way Traffic (per ANSI 156.10)
Length:	Two Way Traffic (per ANSI 156.10)
Length:	Other (as specified)

Bottom Rail:	
	Standard (4")
	6-1/2"
	10"

Hurricane:	
	Hurricane Rated
	Impact Rated
	Hurricane Rated

Extended Warranty	
	2 Years
	3 Years

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.