NABCO Entrances - GT1175 Automatic Sliding Door - Drawing Request FORM

$=USA Dollar 2025 | Revision 4.1.T

Quote: | Page: | of
Company: | Distributor #: | Door #:
Date: | Job Name:
PO #: | Contact:
Drop Ship to:
Ship Method: | Date to Ship:

Notes:

Quantity | Drawing #

Unit Type

- Fixed Sidelite
- Full Open
- Surface Applied
  - to exterior
  - to interior
  - w/ sidelite
  - no sidelite (P-panel w/Wall Track)
- Pocketed Unit
- Breakout Through Opening

On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form.

Handing (viewed from panic breakaway side)

- Bi-Part
- Single: Left hand | Right hand

Finish

- Clear Anodize
- Dark Bronze Ano
- Black Anodize
- Special Anodize
- Special Powder Coat
- Special Paint
- Color
- Hardware Finish on Special Finish Units (Clear or Dark Bronze)

Frame Size

- Width (in) | Header Height (in)
- Clear Door Opening Width (in), if less than max

Wall Opening (required to size doors correctly for SA Units)

- Width (in) | Height (in)

Transom: YES | NO

- Total Frame Height Including Transom (in) (std.=91-1/2")
- Number of Verticals in Transom

Jamb Size

- 1-3/4" x 4-1/2"
- Slick (Std)
- Single Pkt (Std Trans)
- Double Pocket
- 1-3/4"x6-3/8" (Std Pktd)
- 2"x5"
- 2"x7"
- None

Stiles: Narrow (Standard) | Medium

Bottom Rail

- 4" (Standard)
- 5"
- 6-1/2"
- 10"

Glass Thickness

Panel Size
Transom Size

Glass Size Options: (1/4", 3/8", 1/2", 9/16", 5/8", 3/4", 7/8", 1")

Electrified Panels (Special Product Review Form Required)

- Prep for Electrified Glass/Locks/Other

Extended Warranty: 2 Years | 3 Years

Muntin Bars

- None
- 2" (Std)
- 4"
- 6-3/8"
- 8"
- Standard 42.25" Height
- Custom Height

Additional Muntin

- Size
- Location

Threshold

- NONE (Standard)
- 1/2" Between Jambs
- 1/2" Under Jambs* FS ONLY
- 1/4" Between Jambs -FS ONLY
- 1/4" Clear Door Opening

*Does the Total Frame Height entered in Frame Size include height of threshold?

YES <or> NO

Additions/Changes

Locks
- No MSLock
- MSLock (Std)
- MSLock Below Panic
- 4550 Handles
- Armored Strike (NA for Single with Pkt Jam Tubes)
- Exit Indicator

Panic Devices
- Surface applied push bar exit device (FO Only)
- Recessed push bar exit device
- Paddle exit hardware

Electric Lock
- Fail Safe Electric Lock
- Fail Secure Electric Lock

Sensors
- Acusensor M (Std)
- Add sidelite Protection
- Angled spacer for Acusensor M
- Rain Cover for Acusensor M

Upgrade Sensor
- NABCO Conceal
- Acuzone
- I-One
- Ultimo

Switch
- Rocker (Std)
- Keyswitch
- NABCO Remote Connect

Door Closer
- None
- Both
- Door Only
- Swing Panel Only

Holding Beams: Add Qty (1 beam Std)

Tie Rods: Muntin tie rods if not already required

Clean Room: Prep as cleanroom

Alarm Contact: Add Alarm Contact

Cart Bars: Add Qty Aluminum Cart Bars (specify panels)

Reverse Access: Access cover on otherside of header

Add. Sidelite
- # of additional sidelites
- Width (in) | Muntins
- Height (in) | Muntin Height

(Drawing Required for any Extra Sidelites)

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.