NABCO Entrances - GT1175 Automatic Telescopic Sliding Door - Order FORM

$=USA Dollar 2025 | Revision 4.1.T

Quote: | Page: | of

Company: | Distributor #: | Door #:

Date: | Job Name:

PO #: | Contact:

Drop Ship to:

Ship Method: | Date to Ship:

Notes:

Quantity | Drawing #

Unit Type

- Fixed Sidelite
- Full Open

Handing (viewed from panic breakaway side)

- Bi-Part
- Single | Left hand | Right hand

Finish

- Clear Anodize | Special Anodize
- Dark Bronze Ano | Special Powder Coat
- Black Anodize | Special Paint
- Color
- Hardware Finish on Special Finish Units (Clear or Dark Bronze)

Frame Size

- Width (in) | Header Height (in)
- Clear Door Opening Width (in), if less than max

Transom YES | NO

- Total Frame Height Including Transom (in) (std.=91-1/2")
- Number of Verticals in Transom

Jamb Size

- 2"x7"
- None

Stiles Narrow (Std) | Medium

Bottom Rail

- 4" (Standard) | 6-1/2"
- 5" | 10"

Glass Thickness | Glass Size Options:

Panel Size | (1/4", 3/8", 1/2", 9/16", 5/8", 3/4", 7/8", 1")

Transom Size

Electrified Panels (Special Product Review Form Required)

- Prep for Electrified Glass/Locks/Other

Muntin Bars

- None | Standard 42.25" Height
- 2" (Std) | Custom Height
- 4" | ***Additional Muntin***
- 6-3/8" | Size
- 8" | Location

Threshold NONE (Standard)

- 1/2" Between Jambs | 1/4" Between Jambs -FS ONLY
- 1/2" Under Jambs* FS ONLY | 1/4" Clear Door Opening
- 1/4" Under Jambs ** FS ONLY

*Required for FO units. All options available for FS.

**Does the the Total Frame Height entered in Frame Size include height of threshold?

YES <or> NO

Additions/Changes

Locks
- No MSLock
- MSLock (Std)
- 4550 Handles
- Armored Strike
- Exit Indicator

Note:
-MSLock available below Recessed Panic.
-No Armored Strike on Single w/ pocket jambs.

Panic Devices
- Surface applied push bar exit device
- Recessed push bar exit device
- Paddle exit hardware

Electric Lock
- Fail Safe Electric Lock
- Fail Secure Electric Lock

Sensors
- Acusensor M (Std)
- Add sidelite Protection
- Angled spacer for Acusensor M
- Rain Cover for Acusensor M

Upgrade Sensor
- NABCO Conceal | I-One
- Acuzone | Ultimo

Switch
- Rocker (Std) | NABCO Remote Connect
- Keyswitch

Door Closer
- None
- Both
- Door Only
- Swing Panel Only

Extended Warranty 2 Years | 3 Years

Holding Beams Add Qty (1 Beam Standard)

Tie Rods Muntin tie rods if not already required

Alarm Contact Add Alarm Contact

Cart Bars Add Qty Aluminum Cart Bars (specify panels)

Add. Sidelite # of additional sidelites

- Width (in) | Muntins
- Height (in) | Muntin Height

(Drawing Required for any Extra Sidelites)

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.