NABCO- STORM Series Hurricane Doors - Quote Request FORM

$=USA Dollar	Revision
2025	4.1.T

Quote: | Page: | of

Company: | Distributor #: | Door #:

Date: | Job Name:

PO #: | Contact:

Drop Ship to:

Ship Method: | Date to Ship:

Notes:

Type of Unit:

	Single		Fixed Sidelite
	Bi-part		Full Open
		Hand of Unit: (viewed from panic breakaway side)	
	STORM E (H105)		Right hand
	STORM D (H105)		Left hand
	STORM D (H60)		
	STORM (H105)		
	STORM (H60)		

Frame Size:

	Width (in)		Header Height* (in)
	Clear Door Opening Width (in)		

Transom: Not Available

Door/Panel Glass Thickness

Impact		Non-Impact Rated	
9/16"	STORM E (H105)		
7/16"	STORM D (H105)	1/4"	Storm (H105)
1/2"	STORM D (H60)	5/16"	Storm (H60)

Other Glass Thickness Options: Not Available

Finish

	Clear Anodize		Special Anodize
	Dark Bronze Ano		Special Powder Coat
	Black Anodize		Special Paint
			Color
	Hardware Finish on Special Finish Units (Clear or Dark Bronze)		

Threshold: All are equipped with 1/2" jamb to jamb thresholds

Bottom Rail:

	4" (H60 Only)		6-1/2" (Standard)
	10"		

Note:

* H60 max. Height 7' 7-1/2"; H105 max. Height 8' 8"

Quantity | **Drawing #**

Additions/Changes:

Panic Device:		
		Adams Rite G86 Panic Bar (H105 only)
		(4" Muntin Bars Reqired)
Electric Lock:		Fail Safe Electric Lock
		Fail Secure Electric Lock
Flushbolt		Key Cylinder operated flush bolts (H60 Only)
Dead Bolt Lever:		4550 Dead Bolt Lever (Y/N)
Ex.Holding Beam:		# of Additional Holding Beams (1 Beam Standard)

Sensors:		Sidelite Protection
		Angled spacer for Acusensor M
		Rain Cover for Acusensor M
Upgrade Sensor:		Acuzone
		i-One
		ULTIMO
Cart Bars:		Aluminum Cart Bars (specify panels for Bars)
Muntin Bars:		4" (H105 Only)
Switch		Rocker (Std)
		Keyswitch
		NABCO Remote Connect

Extended Warranty

	2 Years		3 Years

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.