

NABCO - GT1400 Folding Door - Drawing Request FORM

\$=USA Dollar	Revision
2025	4.1.T

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Type of Unit:

	Single Fold
	Bi-Fold

Hand of Unit:

	Right hand (door slides to the right when viewed from <u>interior</u>)
	Left hand (door slides to the left when viewed from <u>interior</u>)

Frame Size:

	Width (in)
	Header Height
	Clear Door Opening Width (in)

Transom:

	YES	<or>		NO
	Total Frame Height Including Transom (std.=91-1/2")			
	Number of Verticals in Transom			

Door/Panel Glass Thickness	Transom Glass Thickness

Other Glass Thickness Options: 1/2", 9/16", 5/8", 3/4", 7/8", 1"

Finish:

	Clear Anodize		Special Anodize
	Dk Brnze Ano		Special Pwdr Coat
	Black Anodize		Special Paint
	Color		
	Hardware Finish on Special Finish Units (Clear or Dark Bronze)		

Threshold:

	NONE (Standard)
	1/2" Standard Between Jamb
	*Does the Total Frame Height entered in Frame Size include height of threshold?
	YES <or> NO

Quantity	Drawing #
----------	-----------

Additions/Changes:

Electric Lock:		Fail Safe Electro-Magnetic Lock
Armored Strike:		Armored Strike

Upgrade Sensor:

		I-One
	Acuzone	Ultimo

Alarm Contact:

	Select Yes or No Alarm/Security Contact
--	---

Jamb Tubes:

	2" x 5" (Std)	None Required
--	---------------	---------------

Muntin Bars:

	2" (Standard)
	Other: 4", 8", 6-3/8" (Standard Recessed Panic)
	None
	Standard Height 42-7/8" F.F. - top
	Special location - F.F. - top
	Additional Muntin - F.F. - top

Guide Rails:

	(Qty.) Fold Side (matches finish of door)
Length:	One Way Traffic (per ANSI 156.10)
Length:	Two Way Traffic (per ANSI 156.10)
Length:	Other (as specified)

Bottom Rail:

	Standard (4")	6-1/2"
		10"

Hurricane:

	Hurricane Rated	Impact Rated
		Hurricane Rated

Extended Warranty

	2 Years	3 Years
--	---------	---------

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.