

NABCO Entrances - ICU 2100 Series Manual Door - Drawing Request FORM

|                       |                   |
|-----------------------|-------------------|
| \$=USA Dollar<br>2025 | Revision<br>4.1.T |
|-----------------------|-------------------|

|               |  |                |  |         |  |
|---------------|--|----------------|--|---------|--|
| Quote:        |  | Page:          |  | of      |  |
| Company:      |  | Distributor #: |  | Door #: |  |
| Date:         |  | Job Name:      |  |         |  |
| PO #:         |  | Contact:       |  |         |  |
| Drop Ship to: |  |                |  |         |  |
| Ship Method:  |  | Date to Ship:  |  |         |  |

Notes:

Type of Unit:

|  |          |
|--|----------|
|  | Quantity |
|--|----------|

Model:

|  |          |  |          |  |          |
|--|----------|--|----------|--|----------|
|  | GT2100R  |  | GT2125R  |  | GT2150R  |
|  | GT2100L  |  | GT2125L  |  | GT2150L  |
|  | GT2100TR |  | GT2125TR |  | GT2150TR |
|  | GT2100TL |  | GT2125TL |  | GT2150TL |
|  | GT2100B  |  | GT2125B  |  | GT2150B  |
|  | GT2100TB |  | GT2125TB |  | GT2150TB |

Frame Size:

|  |                                   |
|--|-----------------------------------|
|  | Width                             |
|  | Header Height (slider std. = 88") |
|  | Height Including Transom          |
|  | Number of Verticals in Transom    |
|  | Clear Door Opening Width          |

|                            |                         |
|----------------------------|-------------------------|
| Door/Panel Glass Thickness | Transom Glass Thickness |
|                            |                         |
|                            |                         |
|                            |                         |
|                            |                         |
|                            |                         |
|                            |                         |
|                            |                         |
|                            |                         |

Finish

|  |                 |       |                     |
|--|-----------------|-------|---------------------|
|  | Clear Anodize   |       | Special Anodize     |
|  | (Standard)      |       | Special Powder Coat |
|  | Dark Bronze Ano |       | Special Paint       |
|  | Black Anodize   | Color |                     |

Threshold: (applies to 2150 only)

|  |                      |  |            |
|--|----------------------|--|------------|
|  | Through Door Opening |  | Under Jamb |
|  | Between Jamb         |  | Other      |

Bottom Rail:

|  |          |
|--|----------|
|  | Standard |
|  | 6-1/2"   |
|  | 10"      |

Jamb Tubes:

|  |                                                  |  |
|--|--------------------------------------------------|--|
|  | 1-3/4" x 4-1/2" No Pockets (2- and 4-Panel Std.) |  |
|  | 2" x 7" (Standard for 3- or 6-Panel)             |  |
|  | 1-3/4" x 6-3/8"                                  |  |
|  | 2" x 5"                                          |  |
|  | No Jamb                                          |  |
|  | Other (Specify)                                  |  |

Muntin Bars:

|  |                     |
|--|---------------------|
|  | 2" std.             |
|  | 4"                  |
|  | 6-3/8"              |
|  | 8"                  |
|  | No muntins required |

|  |                                    |
|--|------------------------------------|
|  | Standard Height 42-1/4" F.F. - top |
|  | Special location - F.F. - top      |
|  | Additional Muntin - F.F. - top     |

Options:

(Standard pulls are the "D" and recessed pulls)

|  |                                     |                        |
|--|-------------------------------------|------------------------|
|  | Recessed Handles (both sides)       |                        |
|  | 4570 (Levers Down - Positive Latch) |                        |
|  |                                     | Handle + Recessed Pull |
|  |                                     | Handle on Both Sides   |

(reduces door opening on 2100 only)

|  |                                          |
|--|------------------------------------------|
|  | 4550 Dead Bolt Lever with Exit Indicator |
|  | Medium Stile                             |
|  | No Panic Breakout                        |
|  | Delete Sidelites for Surface Applied     |
|  | Floor Sweeps                             |
|  | Pile + Brush Weather Stripping           |
|  | Composite panels in bottom of doors      |
|  | Self Closing                             |
|  | Hold Open                                |
|  | Air Infiltration Package                 |

Extended Warranty

|  |         |  |         |
|--|---------|--|---------|
|  | 2 Years |  | 3 Years |
|--|---------|--|---------|

Note: Air infiltration/smoke infiltration sealing automatically includes 4570 Latching System

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.