NABCO ICU Door (2400)- Drawing Request FORM

$=USA Dollar	Revision
2025	4.1.T

Quote: | Page: | of
Company: | Distributor #: | Door #:
Date: | Job Name:
PO #: | Contact:
Drop Ship to:
Ship Method: | Date to Ship:

Notes:

Type of Unit:

Single

Model:

Manual (2400M) | Automatic (2400A)

Hand of Unit: (viewed from breakout side)

Right Hand | Left Hand

Frame Size:

Width — Single: 66-108" (1676-2743)

Header Height — Standard 88" (2235);

Finish

Clear Anodize (Standard)	Special Anodize
	Special Powder Coat
Dark Bronze Ano	Special Paint
Black Anodize	Color

Jamb Tubes:

3/4" x 4-1/2" (Manual Only Option)
1-3/4" x 4-1/2" (Standard for Automatic)
1-3/4" x 4-1/2" (Pocketed)

Stiles:

Narrow

Muntin Bars:

2" (Standard)
4"
None

Muntin Height:

Height (42-1/4" F.F. - top is Standard)

Bottom Rail:

4" (Standard) | 6-1/2"
10"

Door/Panel Glass Thickness:

1/4" (Standard) | Other
1"

Quantity | **Drawing #**

Handles:

Recessed Handles
Double "D" Handles
Positive Latch with Recessed Handles
Positive Latch with Handles Down
None (Automatic Option Only)

MS Lock

MS Lock (Cannot be used with Positive Latch Handles)

Weathering:

Vinyl Weathering (Standard)
Vinyl Weathering, No Sweeps
Brush Weathering
Brush Weathering, No Sweeps

Extended Warranty

2 Years | 3 Years

Smoke Package:

UL1784 Smoke Package*
*Requires Positive Latch & Vinyl.

Self-Closer

Self Closing Package (150 lbs Max Weight)

Electrified Panels:

Prep for Electrified Glass/Locks/Other**
**Special Product Review Form Required

Automatic Model Options

Header Sensors:

Acusensor M (Standard)
Acuzone | i-One
Ultimo

Holding Beams (Photoeyes):

None (Standard)
Single | Height #1 (21" Standard)
Dual | Height #2 (51" Standard)

Control Switch: (ON/OFF/HOLDOPEN)

3-Way Rocker Switch (Standard)
3-Way Keyswitch
NABCO Remote Connect Smart Switch

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.