NABCO GT2300 Manual/ICU Swing Door - Quote Request FORM

$=USA Dollar	Revision
2025	4.1.T

Quote: | Page: | of

Company: | Distributor #: | Door #:

Date: | Job Name:

PO #: | Contact:

Drop Ship to:

Ship Method: | Date to Ship:

Notes:

Type of Unit: | **Quantity**

Model Type "A" or "B" as viewed from swing side:

- "A" Inactive Door - Active Door
- "B" Active Door - Inactive Door

Frame Size:

- Width (Frame & Doors) (99-1/2" Maximum)
- Header Height (Standard 87-5/8", Maximum 125")
- Active door width (panel equipped with Latch Handle)
- Inactive door width (panel equipped with Flush Bolt)

Door/Panel Glass Thickness

- 1/4" (std.)
- 1" or other

Finish

- Clear Anodize (Standard)
- Dark Bronze Ano
- Black Anodize
- Special Anodize
- Special Powder Coat
- Special Paint
- Color

Threshold:

- No Threshold (Std)
- Between Jambs
- Under Jambs (Included in Height)
- Other

Bottom Rail:

- 4" (Standard)
- 5"
- 6-1/2"
- 10"

Top Rail:

- 4" (Standard)
- 5"
- 6-1/2"
- 10"

Note: Door gap at bottom is 1/2" standard

Jamb Tubes:

- Standard (1-3/4" x 4-1/2" - No Pockets)
- 1-3/4" x 6-3/8"
- 2" x 5"
- 2" x 7"
- No Jambs Required
- Header Width for No Jambs

Hinges are on outside edges of jamb tubes

Muntin Bars:

- 2" std.
- 4"
- 6-3/8"
- 8"
- No muntins required

Muntin Height:

- Standard Height 42-1/4" F.F. - Top
- Special location - F.F. - Top
- Additional Muntin - F.F. - Top

Extended Warranty

- 2 Years
- 3 Years

Options:

- Medium Stile
- Smoke Rated Required

Some Options Affect Smoke Rating

Composite Panels

Check One	All Lites
	Bottom Lites
	Top Lites
Choose Color	Metallic Silver
	Bone White
	Glossy White
	Dark Bronze
Choose Finish	Textured
	Smooth

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.