

NABCO- GT300/400 Swing Door Operator- ORDER FORM

\$=USA Dollar
2025

Revision
4.1.T

Quote:

Company:

Date:

PO #:

Drop Ship to:

Ship Method:

Page: of

Distributor #: Door #:

Job Name:

Contact:

Date to Ship:

Notes:

Type of Header:	Quantity	Drawing #
8300 300	Door Pivot Location:	
8400 * 400	Outer Jamb Tubes	Center Post
Sizing:	Send Sketch for Center Post Application	
Door Width Header Length	Jamb Size 1-3/4"	Other
Pivot Overlap	Finish	
Access Holes - except Overhead Concealed	Clear Anodize	Special Anodize
Electrical Access Hole in End Cap	Dark Bronze Anodize	Special Pwdr Coat
Electrical Access Hole in Top of Header	Black Anodize	Special Paint
No Holes Required	Color	
Application:	Hardware Finish on Special Finish Units (Clear or Dark Bronze)	
Single Dbl. Egress	Additional Sensors:	
Simultaneous Pair	(Qty.) Acusensor M	P/N A-01306
Dual	(Qty.) Reaction Two	P/N V-00173
Hand of Unit: (Place Back to Pivot Jamb)	(Qty.) OA Edge2 Sensor Stick	
OPERATOR	Notes: OA Edge2 has two sensing modules/stick	
Rt Hand Lt Hand	Additions/Changes:	
CU Inswing Tracks:	Rivnut Kit, CU, Bottom Load P/N M-01199	
12" Track	Rivnut Kit, Sideload and GT710 P/N A-01197	
21" Track	Rivnut Kit, OHC, Bottom Load P/N A-00642	
Direction of Door Swing:	MS Sedco S.S. Wireless Switch Kit (V-00161)	
(Qty.) Inswing	Switch	
(Qty.) Inswing with Panic	3-Way Rocker Switch (Standard)	
(Qty.) Outswing	3-Way Keyswitch	
Pivot type:	NABCO Remote Connect Smart Switch	
Ctr Pivot with FG		
no FG		
Butt Hinge/Offset Pivot Swing Clear		
Reveal: (in inches)		
Outswing Inswing		
Webb Depth of Door Panel: OHC Only		
5/8" 1-9/16"		
7/8" Other web depths		
1" Specify depth		
Sideload Mounting Brackets:		
Full Length Sideload Mounting Bracket Kit		
Two Piece Mounting Bracket Kit		
Extended Warranty		
2 Years 3 Years		

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.