

Quote:

Company:

Date:

PO #:

Drop Ship to:

Ship Method:

Page:

Distributor #:

Job Name:

Contact:

Date to Ship:

of

Door #:

Notes:

Type of Unit:

X

Slide by Slide

Hand of Unit: (viewed from panic breakaway side)

Right hand

Left hand

Quantity

Drawing #

Additions/Changes:

Panic Device:

Recessed push bar exit hardware

Electric Lock:

Fail Safe Electric Lock

Fail Secure Electric Lock

Armored Strike:

Armored Strike

Ex.Holding Beam:

of Additional Holding Beams (1 Beam Standard)

Tie Rods:

Tie Rods Required (Y/N)

Nose Caster:

Req. for panels over 200 lbs. or wider than 42"

Sensors:

Sidelite Protection

Angled spacer for Acusensor M

Rain Cover for Acusensor M

Upgrade Sensor:

Acuzone

i-One

ULTIMO

Alarm Contact:

Select Yes or No Alarm/Security Contact

Cart Bars:

Aluminum Cart Bars (specify panels for Bars)

Frame Size:

Width (in)

Header Height (in)

Clear Door Opening Width (in)

Wall Opening (required to size doors correctly for SA Units)

x

Wall Opening (W x H)

Transom:

YES

<or>

NO

Total Frame Height Including Transom (std.=91-1/2")

Number of Verticals in Transom

Door/Panel Glass Thickness

1/4" (std.)

Transom Glass Thickness

1/4" (std.)

Other

Other

Other Glass Thickness Options: 1/2", 9/16", 5/8", 3/4", 7/8", 1"

Sensors:

Sidelite Protection

Angled spacer for Acusensor M

Rain Cover for Acusensor M

Upgrade Sensor:

Acuzone

i-One

ULTIMO

Alarm Contact:

Select Yes or No Alarm/Security Contact

Cart Bars:

Aluminum Cart Bars (specify panels for Bars)

Finish

Clear Anodize

Special Anodize

Dark Bronze Ano

Special Powder Coat

Black Anodize

Special Paint

Color

Hardware Finish on Special Finish Units (Clear or Dark Bronze)

Extended Warranty

2 Years

3 Years

Muntin Bars:

2" (Standard)

Other: 4", 8", 6-3/8" (Standard Recessed Panic)

None

Standard Height 42-1/4" F.F. - top

Special location - F.F. - top

Additional Muntin - F.F. - top

Medium Stiles

Change to Medium Stile (4")

Switch

Rocker (Std)

Keyswitch

NABCO Remote Connect

Exit Indicator

Exit Indicator

Threshold:

X

1/2" Standard Between Jambs (Standard)

Bottom Rail:

Standard

6-1/2"

10"

Other

Jamb Tubes:

X

1-3/4" x 4-1/2"

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.