

NABCO- STORM Series Hurricane Doors - Drawing Request FORM

\$=USA Dollar	Revision
2026	1.1.T

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Type of Unit:		
	Single	Fixed Sidelite
	Bi-part	Full Open
	Hand of Unit: (viewed from panic breakaway side)	
	STORM E (H105)	Right hand
	STORM D (H105)	Left hand
	STORM D (H60)	
	STORM (H105)	
	STORM (H60)	

Frame Size:		
	Width (in)	Header Height* (in)
	Clear Door Opening Width (in)	
Transom:	Not Available	

Door/Panel Glass Thickness			
Impact		Non-Impact Rated	
9/16"	STORM E (H105)		
7/16"	STORM D (H105)	1/4"	Storm (H105)
1/2"	STORM D (H60)	5/16"	Storm (H60)
Other Glass Thickness Options: Not Available			

Finish			
	Clear Anodize		Special Anodize
	Dark Bronze Ano		Special Powder Coat
	Black Anodize		Special Paint
	Color		
	Hardware Finish on Special Finish Units (Clear or Dark Bronze)		

Threshold:	All are equipped with 1/2" jamb to jamb thresholds		
Bottom Rail:			
	4" (H60 Only)	6-1/2" (Standard)	
	10"		

Note:

* H60 max. Height 7' 7-1/2"; H105 max. Height 8' 8"

Quantity		Drawing #	
----------	--	-----------	--

Additions/Changes:	
Panic Device:	Adams Rite G86 Panic Bar (H105 only) (4" Muntin Bars Required)
Electric Lock:	Fail Safe Electric Lock Fail Secure Electric Lock
Flushbolt	Key Cylinder operated flush bolts (H60 Only)
Dead Bolt Lever:	4550 Dead Bolt Lever (Y/N)
Ex.Holding Beam:	# of Additional Holding Beams (1 Beam Standard)

Sensors:	Sidelite Protection Angled spacer for Acusensor M Rain Cover for Acusensor M
Upgrade Sensor:	Acuzone i-One ULTIMO
Cart Bars:	Aluminum Cart Bars (specify panels for Bars)
Muntin Bars:	4" (H105 Only)
Switch	Rocker (Std) Keyswitch NABCO Remote Connect
Extended Warranty	
2 Years	3 Years

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.