

NABCO Entrances - GT1175 Automatic Sliding Door - Drawing Request FORM

\$=USA Dollar

Revision

2026

1.1.T

Quote:

Company:

Date:

PO #:

Drop Ship to:

Ship Method:

Page:

of

Distributor #:

Door #:

Job Name:

Contact:

Date to Ship:

Notes:

Quantity	Drawing #
Unit Type	
☐ Fixed Sidelite	☐ Pocketed Unit
☐ Full Open	
☐ Surface Applied	On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form.
☐ to exterior	
☐ to interior	☐ Breakout Through Opening
☐ w/ sidelite	
☐ no sidelite (P-panel w/Wall Track)	
Handing (viewed from panic breakaway side)	
☐ Bi-Part	
☐ Single	☐ Left hand ☐ Right hand
Finish	
☐ Clear Anodize	☐ Special Anodize
☐ Dark Bronze Ano	☐ Special Powder Coat
☐ Black Anodize	☐ Special Paint
	Color
☐ Hardware Finish on Special Finish Units (Clear or Dark Bronze)	
Frame Size	
Width (in)	Header Height (in)
Clear Door Opening Width (in), if less than max	
Wall Opening (required to size doors correctly for SA Units)	
Width (in)	Height (in)
Transom ☐ YES ☐ NO	
Total Frame Height Including Transom (in) (std.=91-1/2")	
Number of Verticals in Transom	
Jamb Size	
☐ 1-3/4" x 4-1/2"	☐ 1-3/4"x6-3/8" (Std Pktd)
☐ Slick (Std)	☐ 2"x5"
☐ Single Pkt (Std Trans)	☐ 2"x7"
☐ Double Pocket	☐ None
Stiles ☐ Narrow (Standard) ☐ Medium	
Bottom Rail	
☐ 4" (Standard)	☐ 6-1/2"
☐ 5"	☐ 10"
Glass Thickness	
Glass Size Options:	
Panel Size	(1/4", 3/8", 1/2", 9/16", 5/8", 3/4", 7/8", 1")
Transom Size	
Electrified Panels (Special Product Review Form Required)	
☐ Prep for Electrified Glass/Locks/Other	
Extended Warranty ☐ 2 Years ☐ 3 Years	

Muntin Bars	
☐ None	☐ Standard 42.25" Height
☐ 2" (Std)	☐ Custom Height
☐ 4"	Additional Muntin
☐ 6-3/8"	Size
☐ 8"	Location
Threshold ☐ NONE (Standard)	
☐ 1/2" Between Jamb	☐ 1/4" Between Jamb -FS ONLY
☐ 1/2" Under Jamb* FS ONLY	☐ 1/4" Clear Door Opening
*Does the Total Frame Height entered in Frame Size include height of threshold?	
☐ YES	<or> ☐ NO
Additions/Changes	
Locks	
☐ No MSLock	
☐ MSLock (Std)	☐ MSLock Below Panic
☐ 4550 Handles	
☐ Armored Strike (NA for Single with Pkt Jam Tubes)	
☐ Exit Indicator	
Panic Devices	
☐ Surface applied push bar exit device (FO Only)	
☐ Recessed push bar exit device	
☐ Paddle exit hardware	
Electric Lock	
☐ Fail Safe Electric Lock	
☐ Fail Secure Electric Lock	
Sensors	
☐ Acusensor M (Std)	
☐ Add sidelite Protection	
☐ Angled spacer for Acusensor M	
☐ Rain Cover for Acusensor M	
Upgrade Sensor	
☐ NABCO Conceal	☐ I-One
☐ Acuzone	☐ Ultimo
Switch	
☐ Rocker (Std)	☐ NABCO Remote Connect
☐ Keyswitch	
Door Closer	
☐ None	☐ Door Only
☐ Both	☐ Swing Panel Only
Holding Beams	
☐ Add Qty (1 beam Std)	
Tie Rods	
☐ Muntin tie rods if not already required	
Clean Room	
☐ Prep as cleanroom	
Alarm Contact	
☐ Add Alarm Contact	
Cart Bars	
☐ Add Qty Aluminum Cart Bars (specify panels)	
Reverse Access	
☐ Access cover on otherside of header	
Add. Sidelite	
# of additional sidelites	
Width (in)	Muntins
Height (in)	Muntin Height
(Drawing Required for any Extra Sidelites)	

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.