

NABCO Entrances - GT1175 Automatic Telescopic Sliding Door - Quote Request FORM

\$=USA Dollar

Revision

2026

1.1.T

Quote:

Company:

Date:

PO #:

Drop Ship to:

Ship Method:

Page:

Distributor #:

Job Name:

Contact:

of

Door #:

Date to Ship:

Notes:

Quantity	Drawing #
Unit Type	
☐ Fixed Sidelite	
☐ Full Open	
Handing (viewed from panic breakaway side)	
☐ Bi-Part	
☐ Single	☐ Left hand ☐ Right hand
Finish	
☐ Clear Anodize	☐ Special Anodize
☐ Dark Bronze Ano	☐ Special Powder Coat
☐ Black Anodize	☐ Special Paint
	Color
☐ Hardware Finish on Special Finish Units (Clear or Dark Bronze)	
Frame Size	
Width (in)	Header Height (in)
Clear Door Opening Width (in), if less than max	
Transom	☐ YES ☐ NO
Total Frame Height Including Transom (in) (std.=91-1/2")	
Number of Verticals in Transom	
Jamb Size	
☐ 2"x7"	
☐ None	
Stiles	
☐ Narrow (Std)	☐ Medium
Bottom Rail	
☐ 4" (Standard)	☐ 6-1/2"
☐ 5"	☐ 10"
Glass Thickness	Glass Size Options:
Panel Size	(1/4", 3/8", 1/2", 9/16", 5/8", 3/4", 7/8", 1")
Transom Size	
Electrified Panels (Special Product Review Form Required)	
☐ Prep for Electrified Glass/Locks/Other	
Muntin Bars	
☐ None	☐ Standard 42.25" Height
☐ 2" (Std)	☐ Custom Height
☐ 4"	☐ Additional Muntin
☐ 6-3/8"	☐ Size
☐ 8"	☐ Location

Fixed Sidelite Threshold Only Options	☐ NONE (Standard)
☐ 1/2" Under Jambs	
☐ 1/4" Under Jambs	
**Does the the Total Frame Height entered in Frame Size include height of threshold?	
☐ YES	<or> ☐ NO
Additions/Changes	
Locks	☐ No MSLock ☐ MSLock (Std) ☐ 4550 Handles ☐ Armored Strike ☐ Exit Indicator
Note: -MSLock available below Recessed Panic. -No Armored Strike on Single w/ pocket jambs.	
Panic Devices	☐ Surface applied push bar exit device ☐ Recessed push bar exit device ☐ Paddle exit hardware
Electric Lock	☐ Fail Safe Electric Lock ☐ Fail Secure Electric Lock
Sensors	☐ Acusensor M (Std) ☐ Add sidelite Protection ☐ Angled spacer for Acusensor M ☐ Rain Cover for Acusensor M
Upgrade Sensor	☐ NABCO Conceal ☐ I-One ☐ Acuzone ☐ Ultimo
Switch	☐ Rocker (Std) ☐ NABCO Remote Connect ☐ Keyswitch

Extended Warranty	☐ 2 Years ☐ 3 Years
Holding Beams	☐ Add Qty (1 Beam Standard)
Tie Rods	☐ Muntin tie rods if not already required
Alarm Contact	☐ Add Alarm Contact
Cart Bars	☐ Add Qty Aluminum Cart Bars (specify panels)
Add. Sidelite	# of additional sidelites
Width (in)	Muntins
Height (in)	Muntin Height
(Specials Drawing Required for any Extra Sidelites)	

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.