

NABCO Entrances - ICU 2100 Series Manual Door - Drawing Request FORM

\$=USA Dollar	Revision
2026	1.1.T

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Type of Unit:					
	Quantity				
Model:					
	GT2100R		GT2125R		GT2150R
	GT2100L		GT2125L		GT2150L
	GT2100TR		GT2125TR		GT2150TR
	GT2100TL		GT2125TL		GT2150TL
	GT2100B		GT2125B		GT2150B
	GT2100TB		GT2125TB		GT2150TB
Frame Size:					
	Width				
	Header Height (slider std. = 88")				

Jamb Tubes:	
	1-3/4" x 4-1/2" No Pockets (2- and 4-Panel Std.)
	2" x 7" (Standard for 3- or 6-Panel)
	No Jamb Required
Muntin Bars:	
	2" std.
	4"
	6-3/8"
	8"
	No muntins required

	Clear Door Opening Width		
Door/Panel Glass Thickness	Transom Glass Thickness		
	1/4" (std.)		1/4" (std.)
	1/2"		1/2"
	9/16"		9/16"
	5/8"		5/8"
	3/4"		3/4"
	7/8"		7/8"
	1"		1"

Finish		
	Clr Anodize	Special Anodize
	(Standard)	Special Powder Coat
	Dark Bronze Ano	Special Paint
	Black Anodize	Color

Threshold: (applies to 2150 only)		
	1/2" Through Door Opening	Under Jamb
	1/2" Between Jamb	Other

Bottom Rail:	
	Standard
	6-1/2"
	10"

	Standard Height 42-1/4" F.F. - top
	Special location - F.F. - top
	Additional Muntin - F.F. - top
Options:	
	(Standard pulls are the "D" and recessed pulls)
	Recessed Handles (both sides)
	4570 (Levers Down - Positive Latch)
	Handle + Recessed Pull
	Handle on Both Sides
	(reduces door opening on 2100 only)
	MS Lock
	4550 Dead Bolt Lever with Exit Indicator
	Medium Stile
	No Panic Breakout
	Delete Sidelites for Surface Applied
	Floor Sweeps
	Pile + Brush Weather Stripping
	Composite panels in bottom of doors
	Self Closing
	Hold Open (Self Closing Required)

Extended Warranty		
	2 Years	3 Years

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.