NABCO ICU Telescopic Door (2400_T) - Drawing Request FORM

$=USA Dollar	Revision
2026	1.1.T

Quote: | Page: | of
Company: | Distributor #: | Door #:
Date: | Job Name:
PO #: | Contact:
Drop Ship to:
Ship Method: | Date to Ship:

Notes:

Type of Unit:
X Single

Model:
Manual (2400MT) | Automatic (2400AT)

Hand of Unit: (viewed from breakout side)
Right Hand | Left Hand

Frame Size:
Width — Single: 84"-144" (2134-3658)
Header Height — Standard 88" (2235); Available: 83-102" (2108-2591)

Finish
- Clear Anodize (Standard)
- Dark Bronze Ano
- Black Anodize
- Special Anodize
- Special Powder Coat
- Special Paint
- Color

Jamb Tubes:
X 1-3/4" x 6-3/8"

Stiles:
X Narrow

Stiles:
Narrow (Standard)
Medium

Muntin Bars:
2" (Standard)
4"
None

Muntin Height:
Height (42-1/4" F.F. - top is Standard)

Bottom Rail:
4" (Standard)
10"
6-1/2"

Door/Panel Glass Thickness:
1/4" (Standard)
1"
Other

Quantity | **Drawing #**

Handles:
- Recessed Handles
- Double "D" Handles
- Positive Latch with Recessed Handles
- Positive Latch with Handles Down
- None (Automatic Option Only)

MS Lock
MS Lock (Cannot be used with Positive Latch Handles)

Weathering:
- Vinyl Weathering (Standard)
- Vinyl Weathering, No Sweeps
- Brush Weathering
- Brush Weathering, No Sweeps

Extended Warranty
2 Years | 3 Years

Smoke Package:
UL1784 Smoke Package*
*Requires Positive Latch & Vinyl.

Self-Closer
Self Closing Package (200 lbs Max Weight)

Electrified Panels:
Prep for Electrified Glass/Locks/Other**
**Special Product Review Form Required

Automatic Model Options

Header Sensors:
- Acusensor M (Standard)
- Acuzone | i-One
- Ultimo

Holding Beams (Photoeyes):
- None (Standard)
- Single | Height #1 (21" Standard)
- Dual | Height #2 (51" Standard)

Control Switch: (ON/OFF/HOLDOPEN)
- 3-Way Rocker Switch (Standard)
- 3-Way Keyswitch
- NABCO Remote Connect Smart Switch

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.