

NABCO ICU Telescopic Door (2400_T) - Order FORM

\$=USA Dollar	Revision
2026	1.1.T

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Type of Unit:			Quantity		Drawing #	
X	Single		Handles:			
				Recessed Handles		
				Double "D" Handles		
				Positive Latch with Recessed Handles		
				Positive Latch with Handles Down		
				None (Automatic Option Only)		
Model:			MS Lock			
	Manual (2400MT)	Automatic (2400AT)		MS Lock (Cannot be used with Positive Latch Handles)		
Hand of Unit: (viewed from breakout side)			Weathering:			
	Right Hand	Left Hand		Vinyl Weathering (Standard)		
				Vinyl Weathering, No Sweeps		
				Brush Weathering		
				Brush Weathering, No Sweeps		
Frame Size:						
	Width	Single: 84"-144" (2134-3658)				
	Header Height	Standard 88" (2235); Available: 83-102" (2108-2591)				
Finish						
	Clear Anodize (Standard)	Special Anodize				
		Special Powder Coat				
	Dark Bronze Ano	Special Paint				
	Black Anodize	Color				

Extended Warranty		
	2 Years	3 Years

Jamb Tubes:	Stiles:	
X	1-3/4" x 6-3/8"	
	X	Narrow

Stiles:	
	Narrow (Standard)
	Medium

Muntin Bars:	Muntin Height:	
		Height
	2" (Standard)	(42-1/4" F.F. - top is Standard)
	4"	
	None	

Bottom Rail:		6-1/2"
	4" (Standard)	
	10"	

Door/Panel Glass Thickness:		Other
	1/4" (Standard)	
	1"	

Smoke Package:		
	UL1784 Smoke Package*	
	*Requires Positive Latch & Vinyl.	
Self-Closer		
	Self Closing Package (200 lbs Max Weight)	

Electrified Panels:		
	Prep for Electrified Glass/Locks/Other**	
	**Special Product Review Form Required	

Automatic Model Options		
Header Sensors:		
	Acusensor M (Standard)	
	Acuzone	i-One
	Ultimo	
Holding Beams (Photoeyes):		
	None (Standard)	
	Single	Height #1 (21" Standard)
	Dual	Height #2 (51" Standard)
Control Switch: (ON/OFF/HOLD/OPEN)		
	3-Way Rocker Switch (Standard)	
	3-Way Keyswitch	
	NABCO Remote Connect Smart Switch	

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.