

NABCO- GT300/400 Swing Door Operator Drawing Request Form

\$=USA Dollar
2026

Revision
1.1.T

Quote:

Page:

of

Company:

Distributor #:

Door #:

Date:

Job Name:

PO #:

Contact:

Drop Ship to:

Ship Method:

Date to Ship:

Notes:

Type of Header:

8300300

8400 *400

Sizing:

Door WidthHeader Length

Pivot Overlap

Access Holes - except Overhead Concealed

Electrical Access Hole in End Cap

Electrical Access Hole in Top of Header

No Holes Required

Application:

SingleDbl. Egress

Simultaneous Pair

Dual

Hand of Unit:

(Place Back to Pivot Jamb)

OPERATOR

Rt HandLt Hand

CU Inswing Tracks:

12" Track

21" Track

Direction of Door Swing:

(Qty.) Inswing

(Qty.) Inswing with Panic

(Qty.) Outswing

Pivot type:

Ctr Pivotwith FGno FG

Butt Hinge/Offset PivotSwing Clear

Reveal: (in inches)

OutswingInswing

Webb Depth of Door Panel:

OHC Only

5/8"1-9/16"

7/8"Other web depths

1"Specify depth

Sideload Mounting Brackets:

Full Length Sideload Mounting Bracket Kit

Two Piece Mounting Bracket Kit

Extended Warranty

2 Years3 Years

Quantity

Drawing #

Door Pivot Location:

Outer Jamb TubesCenter Post

Send Sketch for Center Post Application

Jamb Size 1-3/4"Other

Finish

Clear AnodizeSpecial Anodize

Dark Bronze AnodizeSpecial Pwdr Coat

Black AnodizeSpecial Paint

Color

Hardware Finish on Special Finish Units (Clear or Dark Bronze)

Additional Sensors:

(Qty.) Acusensor MP/N A-01306

(Qty.) Reaction TwoP/N V-00173

(Qty.) OA Edge2 Sensor Stick

Notes: OA Edge2 has two sensing modules/stick

Additions/Changes:

Rivnut Kit, CU, Bottom Load P/N M-01199

Rivnut Kit, Sideload and GT710 P/N A-01197

Rivnut Kit, OHC, Bottom Load P/N A-00642

MS Sedco S.S. Wireless Switch Kit (V-00161)

Switch

3-Way Rocker Switch (Standard)

3-Way Keyswitch

NABCO Remote Connect Smart Switch

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.