

NABCO- GT300/400 Swing Door Operator Quote Request Form

\$=USA Dollar
2026
Revision
1.1.T

Quote:

Company:

Date:

PO #:

Drop Ship to:

Ship Method:

Page:

Distributor #:

Job Name:

Contact:

Date to Ship:

Notes:

Type of Header:

Quantity

Drawing #

8300

300

8400 *

400

Door Pivot Location:

Outer Jamb Tubes

Center Post

Sizing:

Door Width

Header Length

Pivot Overlap

Jamb Size 1-3/4"

Other

Send Sketch for Center Post Application

Access Holes - except Overhead Concealed

Electrical Access Hole in End Cap

Electrical Access Hole in Top of Header

No Holes Required

Finish

Clear Anodize

Dark Bronze Anodize

Black Anodize

Special Anodize

Special Pwdr Coat

Special Paint

Application:

Single

Dbl. Egress

Simultaneous Pair

Dual

Hardware Finish on Special Finish Units (Clear or Dark Bronze)

Color

Hand of Unit:

(Place Back to Pivot Jamb)

OPERATOR

Rt Hand

Lt Hand

Additional Sensors:

(Qty.) Acusensor M

P/N A-01306

(Qty.) Reaction Two

P/N V-00173

(Qty.) OA Edge2 Sensor Stick

Notes: OA Edge2 has two sensing modules/stick

CU Inswing Tracks:

12" Track

21" Track

Direction of Door Swing:

(Qty.) Inswing

(Qty.) Inswing with Panic

(Qty.) Outswing

Switch

3-Way Rocker Switch (Standard)

3-Way Keyswitch

NABCO Remote Connect Smart Switch

Pivot type:

Ctr Pivot

with FG

no FG

Butt Hinge/Offset Pivot

Swing Clear

Additions/Changes:

Rivnut Kit, CU, Bottom Load P/N M-01199

Rivnut Kit, Sideload and GT710 P/N A-01197

Rivnut Kit, OHC, Bottom Load P/N A-00642

MS Sedco S.S. Wireless Switch Kit (V-00161)

Reveal: (in inches)

Outswing

Inswing

Webb Depth of Door Panel:

OHC Only

5/8"

1-9/16"

7/8"

Other web depths

1"

Specify depth

Sideload Mounting Brackets:

Full Length Sideload Mounting Bracket Kit

Two Piece Mounting Bracket Kit

Extended Warranty

2 Years

3 Years

Note: Please ensure form is filled out completely accurately to ensure order accuracy. Items marked "Standard" or "Std" will be selected by default if no other option in that section is selected.